

# WAYNE WWB UTILITY PUMP SPECS

## FEATURES / BENEFITS

- **Assembled in the US with foreign and domestic parts**
- Multi-Flo Technology allows easy selection of the appropriate discharge for the application
- Top discharge is perfect for tight spaces where water removal is needed: Laundry Tubs, Window Wells, Buckets, etc.
- Side Discharge is ideal for easy water removal from flat open surfaces: Flat Roofs, Flooded Basements, standing water in yard, shower stalls, etc.
- 30 ft. MAX HEAD removes water down to 1/16 in. of surface, VIRTUALLY DRY
- Portable Electric Water Removal Pump, is completely submersible for the larger water removal jobs
- Easy Hang Tab Feature, for seasonal storage
- Corrosion resistant, sealed thermoplastic construction with 6-leg Stable Base Design
- 10 ft Power cord for hard to reach places, with cord wrap handles
- Max. flow rate is 1350 Gallons Per Hour; 1010 GPH @ 10 ft.
- 3/4 in. Corrosion Resistant Brass discharge outlets, with tethered cap seals, fits any standard garden hose
- Multi-Ring suction strainer filters debris, and minimizes clogs
- For removing water from flooded basements, boats, stock tanks, and even a 5 gallon bucket

## PERFORMANCE

Total Dynamic Head (FT.) 0 5 10 15 20 25  
 Flow rate in GPH 200 400 600 800 1000 1200 1400 1600

HP	Discharge Head	0'	5'	10'	15'	20'	25'
----	----------------	----	----	-----	-----	-----	-----

1/6	Gallons/Hour	1350	1190	1010	815	600	360
-----	--------------	------	------	------	-----	-----	-----