

# Wayne CDU980E Submersible Sump Pump Specification Sheet

## FEATURES / BENEFITS

- ✓ **Assembled in the US with foreign and domestic parts**
- ✓ WAYNE Pumps' energy efficient motors, and engineered design provide the ultra-quiet experience you won't believe. The Hardest Working Pumps, You'll Never Hear™
- ✓ Corrosion Resistant Stainless Steel and Rugged Cast Iron Construction, for long life in tough sump applications
- ✓ High performance; max. flow rate is 5673 Gallons Per Hour; 4743 GPH at 10 ft. of discharge lift
- ✓ Integrated Vertical Float Switch with Solid, Leak Free Polypropylene Float for automatic operation; 9 in. ON level and 4 in. OFF level
- ✓ No need for weep holes; Unique Top Suction Design reduces clogging and prevents air lock condition
- ✓ Engineered with Upper and lower ball bearings, in sealed oil bath, for virtually silent operation
- ✓ Designed with Premium John Crane Carbon/Ceramic Shaft Seals for quality that lasts.
- ✓ Cast Iron Seal Plate Prevents Leaks and Galvanic Corrosion
- ✓ 1-1/2 In. NPT Discharge for compliance with building codes
- ✓ 120 V, PSC, Oil-Filled 3/4 HP Motor
- ✓ Float Guard, Protects Switch from Hang-Ups from Debris and side of pit
- ✓ Abrasion Resistant Glass Reinforced Polycarbonate Impeller for Reliability
- ✓ 8 ft Water Resistant Power Cord provides easy access to nearby GFCI protected outlet
- ✓ For easy installation, use in 11 in. diameter or larger sump basins.
- ✓ CSA agency approved
- ✓ 5 Year Limited Warranty